

## Ultra-Flat Ceiling White

### Description:

**LUMO Ultra-Flat Ceiling White** is a smooth quality paint with excellent hiding power, flow, and touch-up ability specifically designed for professional application. The product contains anti-mould additives for a better durability and performance over time. Its unique formula and dead flat sheen level allow applicators to minimise any critical light reflection or surface imperfections.

### Product Features:

- Product Features
- Low VOC (<30 g/l)
- Excellent hiding power
- Mould resistant
- Smooth ultra-flat

### Benefits:

- Ease of application (roll, brush, and spray)
- Excellent touch up ability
- Can be applied on properly primed or un-primed surfaces
- 1-2hrs recoat depending on T(°C) and relative humidity (%RH)
- Easy water wash up
- Low spatter

### Uses:

Interior living areas, hallways, dining, and bedrooms

### Properties:

Gloss:	2 @60°, <0.8 @80°
Colour:	White
Density:	1.2-1.3 g/ml
Application:	Spray, Roller, Brush
Dry Time:	Touch Dry :20min,
Recoat:	2 hrs. @ 23°C and 55%RH Approx.
Coverage:	≤16 m <sup>2</sup> /l depending on surface condition and absorption
VOC:	<30 g/l calculated on RMs
Clean up:	Water

### Surface preparation:

Full precautions need to be considered to achieve the desired final result on both new plasterboard or previously painted surfaces.

All cracks, joints and nail holes must be filled, cured, and sanded (fine) properly as per manufacturing requirement. The surface must be clean, dry with no sign of dust, peel, mould or loose materials. If any stain is available, clean or wash then if required, apply a proper stain blocker depending on the stain type.

Previously painted surfaces must be light sanded if required. Sand the surface using fine-grit sand block/paper (180 or higher) followed by Surface Preparation to check the painting area.

On new finely prepared plasterboard, to maximise the final properties, it is recommended to apply one coat LUMO Primer Sealer Undercoat to entire surface. This will stop different level of paint absorption, so a better look will be achieved. Let it dry between 12-24 hours depending on weather conditions before paint application.

- Do NOT apply if the ambient temperature is less than 10°C.
- Stir the paint completely.
- Apply 2 coats of product. Wait for 1-2 hrs between coats.

This product can't be used on floor or in the areas subject to immersion.

### Application:

Do NOT apply if ambient temperature is less than 10°C.

Stir paint completely.

Apply 2 coats of product. Wait 1-2 hrs between coats.

### Handling, Health and Environment, Storage:

This product is not classified as DG. Keep out of reach of children. Store in temperature between 10-30°C. Avoid frosting. Do not stack up more than 3 pails at a time. Make sure the lid is tight after each use. To see full Safety Preclusions, please refer to MSDS in the QR code.

## Ultra-Flat Ceiling White

Avoid eye contact and swallowing. If poisoning occurred, contact Poison Information Centre 131 126. Or contact your medical advice immediately.

Eye Contact: flash with running water.

Skin Contact: remove contaminated clothing and wash skin gently.

If Swallowed: do not induce vomiting, rinse mouth with water and seek medical advice. To see full Safety Preclusions, please refer to MSDS in the QR code or contact Lumo Paint Pty Ltd.

### Maintenance:

Maintenance cleaning is essential to the overall life of a painted surface. When selecting a cleaner, mild and soapy water will generally suffice. Avoid abrasive, harsh cleaners and strong basic/acidic solutions.

We recommend testing the cleaning solution in a small area to ensure it doesn't damage the paint film.

### Disposal:

Keep the leftover material in a tight container. Do not dispose in water drain. If used up all paint, let the container dry out at open area with good ventilation. Follow the special guidelines for a proper disposal according to your council advice and protocols.

### Lifetime Limited Warranty:

This Limited Warranty is issued by Lumo Paint Pty Ltd. only to those purchasers who purchase this coating and apply as per recommendations. If this coating peels or blisters during the Lifetime of the purchaser, Lumo Paint Pty Ltd. shall, upon presentation of proof of purchase to the store where the coating was purchased, supply replacement coatings to the purchaser in a quantity that is sufficient to repair the peeling or blistering or refund the original purchase price.

**Pack Size:** 15L, 4L

### Disclaimer:

Lumo Paints Pty Ltd. will not accept responsibility for any colour or look differences. In purchasing from Lumo Paints Pty Ltd, you agree to accept the small risk that there will be a slight variation between the actual colour and pattern between different batches, pails and or sample products. The data provided within this article is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems. All recommendations, information, advice, assistance, or service for the use of our products, whether given by us in writing, oral, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Under no circumstances shall Lumo Paints Pty Ltd be liable for incidental, consequential or indirect damage for alleged negligence, breach of warranty, strict liability, tort or contract arising in connection with product(s). Lumo Paints Pty Ltd sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use.